



**PRODUCT DATA SHEET**

- English -

Collection **LA BOHEME 55**

**econfloor**  
POLSKA

## TECHNICAL DATA

- English -

<b>Product</b>	SPC-Rigid-Vinylflooring: Collection La Boheme 55	
<b>Thickness</b>	5,7 mm	
<b>Wear layer</b>	0.55 mm	
<b>IXPE</b>	1,7 mm (inkl. 0.2 mm Aluminium-Foil)	
<b>Klick-System</b>	Pushdown Click-System	
<b>Features</b>	Waterproof, Wear-Resistant, Anti-Slip, Rot-, Fire-, Sound-, Mold-Proof	
<b>Dimensions</b>	1280 x 230 mm	
<b>Surface Treatment</b>	UV coated, EIR (Embossed in register), Hand-brushed	
<b>Advantages</b>	Easy click-system to install/ Labor costs saving/ Immense stability/ Ecofriendly	
<b>Density</b>	2.05 g/cm <sup>3</sup>	
	<b>Technical data</b>	<b>Test-Results</b>
	EN660-2	Group T
<b>Abrasion Resistance</b>	EN 13893/DIN 51130	R11 Class Ds
<b>Slip Resistance</b>	EN ISO 105-B02	≥6
<b>Color Fastness</b>	EN ISO 26987	Excellent
<b>Castor Chair Resistance</b>	EN71	Non toxic
<b>Chemical Resistance</b>	EN 13501-1	Bfl-s1
<b>Toxicity</b>	ISO/TR4918	Passed
<b>Reaction to fire</b>	EN434	< 0.06%
<b>Dimensional stability</b>	EN425	Good
<b>Castor Chair Effect</b>	EN12524	Suitable
<b>Underfloor heating</b>	EN846	Very good
<b>Antibacterial property</b>	EN	100N/5cm
<b>Peel Strength</b>	EN433	0.03
<b>Residual indentation</b>		N